

DYNASCOPE

Non-Invasive Blood Pressure Monitor LXN-1000



Actual Size

Unified Management of Vital Signs through the LX-1300 Telemetry Transmitter

Point

Enable Unified Vital Data Management via Seamless LX-1300 Connectivity

LX-1300
Telemetry
Transmitter

Connect with LX-1300



Integrate with EMR



*Sold Separately

Compatible with DS-1000 Series Blood Pressure Cuffs

Streamline your workflow by reusing DS-1000 series BP cuffs with the LXN-1000.



Part Number	Description	Arm Circumference
CUF-1000-XS	Adult Extra Small Cuff	4.7" - 6.7"
CUF-1000-S	Adult Small Cuff	6.7" - 8.7"
CUF-1000-M	Adult Medium Cuff	8.7" - 12.6"
CUF-1000-L	Adult Large Cuff	12.6" - 16.5"
CUF-1000-XL	Adult Extra Large Cuff	16.5" - 19.7"

*Note: Requires OAO-123A Attachment and OAT-07A0.75 Cuff Hose for operation.

Specification

Dimensions (W x H x D) (excluding the protrusion)	63 mm x 113 mm x 26 mm / 2.5 inch x 4.4 inch x 1.0 inch
Weight (including the battery)	Approx. 190 g / 0.4 lbs / 6.7 oz
Blood Pressure Measurement Method	Oscillometric Method
Measurement Value	Systolic Blood Pressure (SYS), Diastolic Blood Pressure (DIA), Mean Arterial Pressure (MAP), Pulse Rate (PR)
Pressure Measurement Range	0 to 300 mmHg

Wireless Standard	
Supported Standards	Bluetooth 5.0
Frequency	Bluetooth: 2402 to 2480 MHz
Power Supply	
2 x AA Alkaline Batteries or AA NiMH (Nickel-Metal Hydride) Batteries	
Continuous Use Time	
AA Alkaline Battery	Approx. 2 Days ^o
AA NiMH Battery	Approx. 3 Days ^o

^oInterval setting is 60 minutes, cuff size is M, device settings are in the default state, and the operating environment temperature is 23°C

FUKUDA | Medical Innovation for a Brighter Tomorrow

FUKUDA DENSHI USA, INC.
17725-C NE 65th Street Redmond, WA 98052
Toll Free: (800) 365-6668 / Local: (425) 881-7737 / Fax: (888) 224-7090

The information contained in this document is subject to change without notice.
© 2025 FUKUDA DENSHI USA, INC. All rights reserved. Document No. USRB-0327-00

<http://www.fukudaamerica.com>

